



# Mono Penta Deck



## TABELLE PORTATE

Spessore nominale Supporto <b>Acciaio</b> (mm)	Larghezza efficace appoggio: 100 mm 													
	l=cm	100	125	150	175	200	225	250	275	300	325	350	375	400
0,50	P = kg/m <sup>2</sup>	420	265	180	120	75								
0,60		530	335	230	145	90	60							
0,70		640	405	275	170	110	70	50						
0,80		745	475	325	195	125	80	55						
1,00		960	610	400	240	155	100	70						

Spessore nominale Supporto <b>Alluminio</b> (mm)	Larghezza efficace appoggio: 100 mm 													
	l=cm	100	125	150	175	200	225	250	275	300	325	350	375	400
0,60	P = kg/m <sup>2</sup>	285	135	70										
0,70		335	160	85										
0,80		380	185	100	55									
1,00		465	225	120	70									

Spessore Pannello (mm)	Spessore Nominale Supporto <b>Acciaio</b> (mm)				
	0,50	0,60	0,70	0,80	1,00
	Peso Pannello (kg/m <sup>2</sup> )				
10	5,4	6,4	7,4	8,4	10,4
20	5,8	6,8	7,8	8,8	10,8
30	6,2	7,2	8,2	9,2	11,2
40	6,6	7,6	8,6	9,6	11,6
50	7,0	8,0	9,0	10,0	12,0
60	7,4	8,4	9,4	10,4	12,4
80	8,2	9,2	10,2	11,2	13,2
100	9,0	10,0	11,0	12,0	14,0
120	-	-	-	-	-
150	-	-	-	-	-

Spessore Pannello (mm)	Spessore Nominale Supporto <b>Alluminio</b> (mm)			
	0,60	0,70	0,80	1,00
	Peso Pannello (kg/m <sup>2</sup> )			
10	2,8	3,2	3,6	4,2
20	3,2	3,6	4,0	4,6
30	3,6	4,0	4,4	5,0
40	4,0	4,4	4,8	5,4
50	4,4	4,8	5,2	5,8
60	4,8	5,2	5,6	6,2
80	5,6	6,0	6,4	7,0
100	6,4	6,8	7,2	7,8
120	7,2	7,6	8,0	8,6
150	8,0	8,4	8,8	9,4

- Valori in Nero: Stati Limite Ultimo
- Valori in Rosso: Stati Limite di Esercizio (freccia = 1/200 Luce)
- Values in Black: Ultimate Limit States
- Values in Red: Serviceability Limit States (deflection = 1/200 span)